



KRYTAC®

TRIDENT MK II : SPR Foliage Green



SPECIFICATIONS

All specifications subject to change.

| | |
|------------------------|--------------------------------|
| Caliber: | 6 mm |
| Overall Length: | 863 mm (34") - 945 mm (37.25") |
| Overall Height: | 223 mm (8.75") |
| Weight: | 2.7 kg (5.9 lbs) |
| Outer Barrel Length: | 406 mm (16") |
| Inner Barrel Length: | 416 mm |
| Inner Barrel Diameter: | 6.05 mm |

EXTERNAL FEATURES

- KRYTAC MK II metal alloy receivers
- Licensed DEFIANCE® TR113 keymod hand guard
- Licensed DEFIANCE® pistol grip
- KRYTAC battery stock
- Ambidextrous fire selector
- Licensed CMC trigger
- MIL-STD 1913 Picatinny top rail
- Ambidextrous sling loops
- Adjustable iron sights

INTERNAL FEATURES

- 8mm ball bearing mechbox
- Integrated FET system
- Easy maintenance spring guide
- Padded cylinder head
- Relief-cut cylinder window
- Anti-corrosion mechbox coating
- Adjustable rotary hop-up
- Temperature and wear resistant hop-up bucking
- KRYTAC 30K high torque motor



RATE OF FIRE
20+ RPS



VELOCITY (with 0.20g BB)
Min: 400 FPS / 122 MPS
Max: 420 FPS / 128 MPS

*Performance details are based on U.S. specifications and can be modified to meet the laws and regulations of your local region.